

WOODTEX ALL WEATHER ABSORPTIVE PANELS - NOISE REDUCTION IN PLANTROOMS



Plantrooms, both internal or roof mounted are sources of excessive noise that can travel into adjoining occupied levels or in the case of roof plantrooms into nearby residential properties.

To achieve compliance with EPA or OH&S noise level guidelines, it is often required to reduce plantroom sound levels by installing an absorptive lining facing the noise source.

Woodtex is a proven high performance absorptive wall lining, with extreme durability to impact, and Australian weather conditions

Woodtex is extensively installed within Woolworth & Coles Supermarket Exterior / Roof Plantrooms as well as in Loading Docks, Car Parks and Road / Rail Noise Walls .

EASY & FAST INSTALLATION :

Use cutting & fixing methods similar to those used if working with plywood.

Woodtex panels are simple butt jointed, and need to be securely fixed to the backing wall with screws set at approx 600mm centres.

Oversize washers (30mm - 50mm dia) are recommended to maximise screw hold.

If Fixing To Hebel or Masonry Walls

Pre-drill Woodtex & Hebel simultaneously & insert plastic rawl plugs to hold screws.

If Fixing To Precast Concrete Walls

Pre-drill & use knock in anchors or plug/screws

If Fixing To Steel Channels or Timber Battens

Direct fix using Roofing Type Hex Head Tek or Wood Screws to suit.

- Size : 2400 mm x 600 mm
- Thickness: 25/38/50 mm
- NRC = 0.40 @ 25mm
- NRC = 0.85 (with airspace)
- AS 1530.3 - (0,0,0,0)
- AS 3837 - Group I
- AS 1530.1 - Non Combustible
- Weatherproof & Robust

FREE CALL: 1800-800-569

SYDNEY

2/29 Charles St
ST MARYS NSW 2760

MELBOURNE

1/5 Katherine Drive
RAVENHALL VIC 3023

PERTH

2/109 Garling Rd
O'CONNOR WA 6163

www.woodtex.com.au

